

## DECLARATION OF PERFORMANCE

(Regulation (EU) 305/2011)

No. TEKTO01/2013

1. Unique identification code of the product-type:

**TEKTOTERM**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to article 11(4):

**TEKTOTERM**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Thermal rendering/plastering insulating mortar**

4. Name, registered trade name or trade mark and contact address of the manufacturer as required pursuant to article 11(5):

**ARCHITEKTONIDIS MONOTIKA S.A., "TEKTO HELLAS",  
OFFICES: 10, Zakka str, Neapoli, Thessaloniki, P.O. 56727, Tel: 2310-511871,  
Fax: 2310-521836, Greece, e-mail: tekto@tekto.gr  
FACTORY: 10<sup>o</sup> klm Thessaloniki – Neochorouda, Greece,  
Tel and Fax: 2310-782007**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**ELOT EN 998-1: 2010 "Specification for mortar for masonry. Part 1: rendering and plastering mortar"**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not Applicable**

## 9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2 s1 d0	ELOT EN 998-1 : 2010
Adhesion	0,13 N/mm <sup>2</sup> , <b>FPB</b>	
Capillary water absorption	<b>W1</b>	
Coefficient of water vapour diffusion	$\mu = 9$	
Thermal conductivity	$\lambda_d = 0,056$ W/mK, <b>T1</b>	
Durability	Against freeze/thaw: evaluation based on provisions valid in the intended place of use of the mortar	
External fire performance	NPD	
Noise absorption	Rw 0 42 Db; $\Delta$ Rw 7dB	
Emissions of dangerous substances	NPD	
Resistance to fire	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Theodoros G. Architektonidis  
 Chemical Engineer, MSc  
 TEKTO Quality Manager  
 Thessaloniki - Greece, 03/09/2013

