



POLITERM® MACHINE SCREW

SCREW FOR CEMENT LOADING

POLITERM MACHINE SCREW Screw for cement loading		
TYPE OF EQUIPMENT	Equipment for the mechanical loading of cement into the Politerm® Machine tank.	
TECHNICAL CHARACTERISTICS	Electrical power supply Power of the engine Voltage Speed Loading height Hopper capacity	400V 2,2kW 380V 50Hz three phase + earth 260 turns/min 80cm Approx. 150kg of cement
DIMENSIONS	External Ø Screw lenght Final packaging size Weight	16cm 220cm 260cm x 100cm Approx 120kg
STANDARD EQUIPMENT	 10 m of cable with three phases socket + earth 32A. Use and maintenance manual. CE Conformity declaration 	

gathered from laboratory tests meaning that in practical applications on building sites the final characteristics of the product may be subject to substantial variations depending on the meteorological conditions and the installation. The user must always check the suitability of the product for its specific use, undertaking all liability implicit in and deriving from the use of the product, as well as comply with all methods and instructions for use judgement without any notification. The distribution of this data sheet supersedes and cancels the validity of any other data sheet published previously.







10Km Thessalonikis-Neochoroudas, Greece Tel: +302310782007 email: tekto@tekto.gr

